

Lift Truck & Sliding Tandem Lubricant

PRODUCT DESCRIPTION:

JAX Lift Truck & Sliding Tandem Lubricant is an excellent lubricant because it increases ram and rail life, with no binding, waste or mess. It effectively prevents seal leakage and decreases wear and friction on channels and uprights by up to 80%. It is easy to apply and adheres where most other greases drip or sling off.

PRODUCT BENEFITS:

A combination of two premium, tacky greases with molybdenum disulfide, this formula is designed to produce a tenacious film of lubricant on any sliding metal surface. The grease provides the benefit of antiwear and extreme-pressure additives, while the molybdenum disulfide creates a burnishing film, providing extra insurance long after the grease may wear away.

APPLICATION:

JAX Lift Truck & Sliding Tandem Lubricant works on lift trucks and other material handling equipment to eliminate oil drippage on warehouse and receiving dock floors, keep rollers from getting out-of-round, cut greasing intervals, and help prevent guide rail wear. Additionally, consistent use will eliminate friction overloads on hydraulic rams which could cause seals to wear and leak.

Used on sliding tandems, Lift Truck & Sliding Tandem Lubricant will prevent rust and eliminate freeze-up. It is formulated to stay mobile down to -40°F (-40°C) and will repel water, rain, snow and ice. It is ideal for large fleets that see all kinds of weather, and can also be used as a quick and easy lube for 5th wheel pads.

Telescoping boom cranes: As Dawes Crane Rental has proven numerous times, keeping a consistent coating on all the rub points of extending booms eliminates on-the-jobsite issues of chatter, sticking and jumping. It makes the extending and retracting of booms a safe, smooth, life-extending operation.

TECHNICAL DATA:

| | |
|----------------|-----------------------|
| Propellant: | Propane and n-Butane |
| Flash Point: | N/A |
| Spray Pattern: | Shotgun Blast |
| Texture: | Rich Brown Heavy Film |
| Appearance: | Black Tar |
| Consistency: | Heavy |

AEROSOL PACKAGING:

11 oz. net weight aerosol cans (12/case) – Part # JAX106



Lift Truck & Sliding Tandem Lubricant



NSF International / Nonfood Compounds Registration Program

October 11, 2004

Ms. Patty Riek
PRESSURE-LUBE, INC. JAX
W134 N5373 CAMPBELL DRIVE
MENOMONEE FALLS, WI 53051
UNITED STATES

RE: JAX LIFT TRUCK & SLIDING TANDEM LUBRICANT (Aerosol)
Category Code: H2
NSF Registration No. 133889

Dear Ms. Patty Riek:

NSF has processed the application for Registration of **JAX LIFT TRUCK & SLIDING TANDEM LUBRICANT (Aerosol)** to the NSF Registration Guidelines for Proprietary Substances and Nonfood Compounds (2004), which are available at <http://www.nsf.org>. The NSF Nonfood Compounds Registration Program is a continuation of the USDA product approval and listing program, which is based on meeting regulatory requirements including FDA 21 CFR for appropriate use, ingredient and labeling.

This product is acceptable as a lubricant where there is no possibility of food contact (H2) in and around food processing areas. Such compounds may be used as lubricants, release agents, or antirust films on equipment and machine parts in locations in which there is no possibility of the lubricant or lubricated part contacting edible products.

NSF Registration of this product is current when the NSF Registration Number, Category Code, and Registration Mark appear on the NSF-approved product label, and the registered product name is included in the current NSF White Book Listing of Nonfood Compounds at the NSF website (<http://www.nsf.org>). The NSF Registration Mark can be downloaded from the NSF website, at http://www.nsf.org/business/about_NSF/nsf_marks_download.asp.

NSF Listing of all registered Nonfood compounds by NSF International is not an endorsement of those compounds, or of any performance or efficacy claims made by the manufacturer.

Registration status may be verified at any time via the NSF web site, at <http://www.nsf.org>. Changes in formulation or label, without the prior written consent of NSF, will void registration, and will supersede the on-line listing.

Sincerely,

Carmen Grindatti
NSF Nonfood Compounds Registration Program

Company No: N05625

Distributed By:

PRESSURE-LUBE
America's Finest Lubricants

W134 N5373 Campbell Drive • Menomonee Falls, WI 53051
262.781.8850 • 800.782.8850 • FAX 262.781.3906
www.jax.com