

Dry-Glide® Silicone WB

PRODUCT DESCRIPTION:

JAX Dry-Glide WB is a premium quality aerosol silicone lubricant with a high percentage of premium quality food-grade silicone fluid – three times the percentage found in competitive sprays! JAX has developed a water-based formula that eliminates the concern for flammability, sprays on clear, dries quickly, does not drip, and has virtually no odor while drying.

JAX Dry-Glide WB is specially formulated to lubricate gravity-feed tracks. Consistent use will keep displays slick, eliminate sticking, and help keep products fronted. JAX Dry-Glide WB is also ideal for reducing friction between unlike surfaces, such as rods and bushings, or plastic goods on roller table chains.

PRODUCT BENEFITS:

- Non-flammable formula – safe to store in delivery vehicles and storerooms
- Improved bottle sliding for increased customer satisfaction
- Helps keep product fronted, making displays look full at all times
- Colorless, tasteless and odorless when dry
- Meets USDA H1 requirements to eliminate concerns over incidental contact
- Safe on plastic and styrene

APPLICATIONS:

- Plastic display shelves
- Metal shelving
- Cold vault trays
- Gravity-feed store aisle sheets
- Tracks
- Eviscerator rods
- Nonmetallic hanger chains

TECHNICAL DATA:

Propellant:	Propane and n-Butane
Flash Point:	None (water-based)
Pour Point:	Protect from Freezing
Spray Pattern:	Medium Mist
Texture:	Medium White Film
Appearance:	White
Consistency:	Light
Storage Temperature:	40–120° F (4–49°C) DO NOT FREEZE!

AEROSOL PACKAGING:

12 oz. net weight aerosol cans (12/case) – Part # JAX208
 For a bulk version, see DC or RTU DC Conveyor Release





NSF International / Nonfood Compounds Registration Program

September 13, 2004

Ms. Patty Riek
PRESSURE-LUBE, INC. JAX
W134 N5373 CAMPBELL DRIVE
MENOMONEE FALLS, WI 53051

RE: JAX DRY-GLIDE WB (AEROSOL)
Category Code: H1
NSF Registration No. 133439

Dear Ms. Patty Riek:

NSF has processed the application for Registration of **JAX DRY-GLIDE WB (AEROSOL)** to the NSF Registration Guidelines for Proprietary Substances and Nonfood Compounds (2004), which are available at <http://www.nsf.org>. The NSF Nonfood Compounds Registration Program is a continuation of the USDA product approval and listing program, which is based on meeting regulatory requirements including FDA 21 CFR for appropriate use, ingredient and labeling.

This product is acceptable as a lubricant with incidental food contact (H1) for use in and around food processing areas. Such compounds may be used on food processing equipment as a protective anti-rust film, as a release agent on gaskets or seals of tank closures, and as a lubricant for machine parts and equipment in locations in which there is a potential exposure of the lubricated part to food. The amount used should be the minimum required to accomplish the desired technical effect on the equipment. If used as an anti-rust film, the compound must be removed from the equipment surface by washing or wiping, as required to leave the surface effectively free of any substance which could be transferred to food being processed.

NSF Registration of this product is current when the NSF Registration Number, Category Code, and Registration Mark appear on the NSF-approved product label, and the registered product name is included in the current NSF White Book Listing of Nonfood Compounds at the NSF website (<http://www.nsf.org>). The NSF Registration Mark can be downloaded from the NSF website, at http://www.nsf.org/business/about_NSF/nsf_marks_download.asp.

NSF Listing of all registered Nonfood compounds by NSF International is not an endorsement of those compounds, or of any performance or efficacy claims made by the manufacturer.

Registration status may be verified at any time via the NSF web site, at <http://www.nsf.org>. Changes in formulation or label, without the prior written consent of NSF, will void registration, and will supersede the on-line listing.

Sincerely,

Carmen Grindatti
NSF Nonfood Compounds Registration Program

Company No: N05625

Distributed By:

PRESSURE-LUBE
America's Finest Lubricants